

## **DECLARATION OF PERFORMANCE**

## DOP 046032713GB

1. Unique identification code of the product-type:

## **TUBAGE ALU A5**

Metal flue liners - EN 1856-2: 2009

2. Type, batch or serial number or any other element allowing identification of the construction product:

EN 1856-2 : 2009 (8.2)
T160 N1 D Vm L11030 O

**3.** Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Convey the products of combustion from appliances to the outside atmosphere

4. Name, registered trade name or registered trade mark and contact address of the manufacturer:

POUJOULAT SA - CS 50016 - 79270 SAINT-SYMPHORIEN, France

5. Name, registered trade name or registered trade mark and contact address of the distributor:

Not applicable

**6.** System or systems of assessment and verification of constancy of performance of the construction product:

System 2+: Metal flue liners, connecting flue pipes and fittings and System 4: Terminals

- 7. The declaration of performance concerning a construction product is covered by a harmonised standard: Laboratoire National de métrologie et d'Essais (n°0071)
- **8.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by: *Michel VAN PRUYSSEN, Operation director* 

Saint Symphorien, 07/01/2013

## 8.2 - Declared performance in compliance with EN 1856-2 : 2009 use as metal flue liners

Essential characteristics	Performance	Harmonised technical specification
Installed length	100, 110, 125, 130, 140, 150, 155	
Gas tightness / Leakage	Pass N1 (<2 l/s.m² - 40 Pa)	
Sootfire resistance	T160 O	
Mechanical resistance	See installation instructions	
Flow resistance	r = 0,005 m	EN 1856-2 : 2009
Condensate penetration resistance	D	
Corrosion resistance	1 x 0,30 mm Vm (aluminium A5)	
Freeze thaw resistance	Pass	